


Thanks to a magnificent hydraulic balancing, an efficient operation is ensured where more than one or cooling group is used or in multi-pump systems. As well as hydraulic balance, it is very important to separate the air and residue in the system. Hydraulic balance and air separation could be ensured with a single product. Thus, four installation connection will be enough instead of eight. Advantage is gained in respect of both first investment and installation and workmanship costs.





MAXIMUM OPERATING PRESSURE : 10 BAR

MAXIMUM OPERATING TEMPERATURE : 110 °C

HOUSING: CARBON STEEL

Connection Diameter		Dimensions						
DN	Inch	ØD	LK	LF	L	H	h1	ØA
20	3/4"	88.9	190	240	180	340	80	1/2"
25	1"	88.9	190	240	180	410	80	1/2"
32	1 1/4"	88.9	190	240	180	510	80	1/2"
40	1 1/2"	114.3	225	260	215	570	105	1/2"
50	2"	114.3	280	280	265	660	125	1/2"
65	2 1/2"	139.7	315	315	350	730	140	1/2"
80	3"	168.3	365	365	370	860	165	1/2"
100	4"	219.1	420	420	465	1020	175	1/2"
125	5"	273	475	475	545	1260	215	1"
150	6"	273	500	500	730	1400	260	1"
200	8"	400	715	715	880	1540	275	1"
250	10"	400	750	750	1270	1600	300	2"
300	12"	500	780	780	1370	1800	325	2"